


Yunmo Chen<sup>1</sup>, William Gantt<sup>2</sup>, Weiwei Gu<sup>2</sup>, Tongfei Chen<sup>3</sup>, Aaron White<sup>2</sup>, Benjamin Van Durme<sup>1</sup>

<sup>1</sup>Johns Hopkins University, <sup>2</sup>University of Rochester, <sup>3</sup>Microsoft Semantic Machines

## Summary


- (Generalized) **template extraction** is the task of extracting **dictionary-like** structures from text **documents**
- **Template extraction** can be formulated as a **Markov Decision Process (MDP)**, where an **agent iteratively** extracts templates
- **Imitation learning** with an **interactive expert** can provide concrete (supervised) learning signals using **dynamic oracles**, enabling effective training of an **agent**
- The approach outperforms previous models on the SciREX and MUC-4 datasets and presents a strong baseline on the new Granular dataset

## Demo of the Approach




Example from the SciREX dataset

## Examples of Other Template Extraction Datasets (Tasks)




Example from the MUC-4 dataset



Example from the Granular dataset


## Markov Decision Process



## Metrics


- CEAF-REE is a standard metric for template extraction that measures entity-level slot filler precision, recall, and F1
- Since it is common in template extraction to identify representative mentions (rather than full coreference chains), we also present a mention-level variant of this metric called CEAF-RME

## Results on MUC-4



Metric: CEAF-RME<sub>g3</sub>

## Results on SciREX



Metric: CEAF-RME<sub>g3</sub>